



GMV-2F

9"X 50" Precision Milling Machine

- + 3-Horsepower Variable Speed Head
- + Class-7 Super Precision Spindle Bearings
- + Hard-Chrome Plated and Mirror Ground Quill
- + Hard-Chrome Plated X & Y Axis Ways
- + 9" x 50" Table Dimensions
- + Coolant Proof Halogen Lamp Standard
- + 4,000 RPM Digital Variable Speed Option Available

Table	
Table Size (W x L)	9" x 50" (230 x 1270mm)
T-slot Width / Quantity	5/8" / 3 on 2.5" centers
Table Load Capacity	440 lbs. (200kg)
Table Surface to Floor Dimension	32" – 48" (820-1226mm)
Machine Travels & Capacity	
Table Travel – Longitudinal – X Axis	38" (966mm)
Table Travel with Power Feed	33.07" (840mm)
Cross Travel – Y Axis	12" (305mm)
Vertical Knee Travel – Z Axis	16" (406mm)
Overarm (ram) Travel	12" (305mm)
Overarm Swivel	360°
Spindle Nose-to-Table Surface	0" - 18.5" (0 - 469mm)
Spindle Centerline to Column Face	6.75" - 18.75" (171 - 476mm)
Leadscrews with ground pitch surface (X & Y)	0.200" per rev. (ballscrews optional)
Adjustable scale ring display resolution	0.001" (5mm)
Ways – X, Y & Z Axes – Hard Chrome Plated	Hardened & Ground Dovetail Ways
Spindle Head (Vari-Speed)	
Spindle Motor	3-HP / 3-Phase 220 volts (440 Optional)
Spindle Taper (hardened & ground)	R-8
Spindle Runout	0.00008" maximum runout (0.002mm)
Spindle Bearings ABEC-7 matched set	Class-7 Bearings
Variable Speed Spindle	60 – 4,500 RPM
Head Tilt (Left-to-Right)	90° – 0 – 90°
Head Tilt (Front-to-Back / Up-Down)	+45° – 0 – -38°
Head Swivel on Turret	360°
Quill	
Quill Diameter	3-3/8" (85.725mm)
Quill Travel – Manual & Power Feed	5" (127mm)
Quill feeds – With Trip Release – Inch	0.0015" / 0.003" / 0.006"
Quill feeds – With Trip Release – Metric	0.04mm / 0.08mm / 0.16mm
Dimensions & Weight	
Machine Weight	2,222 lbs. (1010 Kgs)
Electrical Requirements – 220 volts	3-Ph / 60 Hz / 9.5 amps